

TECHNICAL DATA

SILKOLENE PRO BOOST

Octane improver

Description

SILKOLENE PRO BOOST is a unique blend of synthetic low-toxicity organic chemicals creating a highly efficient octane improver specifically designed to combat preignition - often called 'pinking' or 'knocking'. This in turn leads to improved acceleration. SILKOLENE PRO BOOST also reduces upper cylinder wear and burns cleanly without leaving deposits in the combustion chamber.

Adding SILKOLENE PRO BOOST to petrol will have a 'keep clean effect' in both carburettor and injector fuel systems and will also help to reduce icing in carburettors. SILKOLENE PRO BOOST also reduces fuel system corrosion.

Application

SILKOLENE PRO BOOST has been successfully tested in a wide variety of car and motorcycle engines, including 2-stroke. It is suitable for all petrol engines and all qualities of fuel.

SILKOLENE PRO BOOST does not affect mixture settings making carburettor adjustment unnecessary. It is fully compatible with all petrol fuels and does not attack fuel hoses or filters.

Recommended Dosages

SILKOLENE PRO BOOST can be used between 1% and 3%. Actual octane number improvement depends on the fuel characteristics; however, a 1.5% treat would normally be expected to give an increase in Motor Octane Number (MON) of between 0.5 and 2.0.

Accidental overdosing will have no adverse effects.

Advantages / Benefits

- · Highly efficient octane booster
- Improves acceleration by combating pre-ignition
- Compatible with Catalytic Converters
- Helps reduce upper cylinder wear and keeps fuel system and combustion chamber clean and deposit free
- SILKOLENE PRO BOOST does not contain lead or aniline Furthermore, the addition of SILKOLENE PRO BOOST promotes more complete combustion helping reduce harmful exhaust gases such as carbon monoxide

March 2015 GDUK Page 1 of 2

FUCHS LUBRICANTS (UK) PLC

New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU Tel: +44 (0)1782 203 700

Email: contact-uk@fuchs-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.



TECHNICAL DATA

The following chart can be used to determine recommended dosing.

Percent SILKOLENE PRO BOOST	Cc's of SILKOLENE PRO BOOST to 1litre of fuel
1.0	10
1.5	15
2.0	20
2.5	25
3.0	30

March 2015 GDUK Page 2 of 2

FUCHS LUBRICANTS (UK) PLC

New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU Tel: +44 (0)1782 203 700

Email: contact-uk@fuchs-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Health, Safety and Environmental information is provided for this product in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.