

Silkolene®

SILKOLENE MAG COOL

A premium performance coolant based on mono-ethylene glycol. Free from nitrites, amines, phosphates and silicates.

Description

SILKOLENE MAG COOL is a mono-ethylene glycol based ready to use long life coolant and anti-freeze designed for use in motorcycle, scooter and quad bike engines especially those containing magnesium alloy technology.

MAG COOL is free from nitrates, silicates and phosphates and is formulated using the latest advanced Organic Acid Technology (OAT). SILKOLENE MAG COOL protects highly stressed engines from frost, overheating, corrosion and cavitation.

SILKOLENE MAG COOL is suitable for and compatible with all materials commonly found in motorcycle engine coolant systems.

Application

SILKOLENE MAG COOL is a ready to use high performance motorcycle coolant and antifreeze for all round use.

Do **not** dilute SILKOLENE MAG COOL with water, this will reduce its frost and corrosion protection.

We do not recommend that MAG COOL is mixed with other coolants as some may not be compatible.

Advantages

- Ready to use, mixed with demineralised water
- Prevents cavitation and provides excellent corrosion resistance and deposit control
- Compatible with magnesium alloys, aluminium, plastics, elastomers and gasket materials used in modern engine cooling systems
- Provides frost protection down to -40°C
- Contains a bittering agent

Product Information



Further Information

Typical Data: **SILKOLENE MAG COOL**

Characteristics	Method	Unit	Result
Appearance	Visual		Light Orange
Specific Gravity @ 20°C	IP 160		1.068
pH-Value	DIN 51 369		8.6
Boiling Point	ASTM D1120	°C	>105
Frost Protection		°C	-40

Updated 13/05/2022 ABUK

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.